

TECHNICAL DATA SHEET

Update of this document : 07/10/2013
Référence ISO de ce document : DON/LS 03



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024

F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37
www.lemaitre-securite.com
info@lemaitre-securite.com



PAULINE SB AERE SRC
WHITE CLOG IN PERFORATED
MICROFIBER WITH AN ADJUSTABLE
BACK STRAP

PROTECTIONS FOR THIS MODEL



Sizes available : from 35(2) to 42(8)
Weight of one pair in size 42(8): 650 gr.
Norme EN ISO 20345 : 2011
CERTIFICATION N°: 0161/19544/12

Upper features

- Upper : white perforated microfiber
- Tongue : white perforated microfiber
- Lining : Cambrelle
- Vamp lining : synthetic
- Closing : adjustable back strap and 2 elastics bands to close the tongue
- Tongue marking: size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- Toecap : stainless steel (200 joules)

Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : foam and textile

Sole features

- Name : PARABOLINE
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : white
- Outsole density : 1
- Outsole color : white
- Slip resistance SRA (flat) : 0,45; (heel) : 0,58
- Slip resistance SRB (flat) : 0,22 ; (heel) : 0,16

Requirements of the norm EN ISO 20345 :

	Steel toecap		Polycarbonate toecap		Aluminum toecap (200 joules)
	Steel midsole		Non metallic midsole		
	A Electric resistance – Antistatic shoes.				
	CI Insulating sole against cold.				
	E Heel energy absorption.				
	FO Hydrocarbons resistance of the undermine sole.				
	HI Insulating sole against heat.				
	HRO Heat resistance of the sole.				
	M Metatarsal protection.				
	P Perforation resistance.				
	WRU Water repellent upper.				
	WR Water repellent junction upper/sole.				



Regarding the norm EN ISO 20345 :2011, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) = 0,32
SRA (heel) = 0,28
SRB (flat) = 0,18
SRB (heel) = 0,13

Advantages = End users benefits

Safety clog exceptionally well ventilated model, easy to fit in

- **Cambrelle lining**, offers greater comfort and hygiene. 100% polyamide, this material is breathable, transferring humidity from the skin to the outside. It is also highly resistant to abrasion.
- SOLE : PARABOLINE**
 - ✓ **Double density PU injected**: excellent comfort even in extreme flexing conditions
 - ✓ **Polyurethane with good antistatic properties, good resistance to hydrolysis and heat**
 - ✓ **Defined heel**: sure-footed safety! an additional precaution especially on ladders
 - ✓ **Very resistant to landslides** thanks to the studded open structure for better drainage of liquids
 - ✓ **Antistatic**
- **Parabolic® profile**
 - **Exceptional slip resistance** : footprint adapts itself to the nature of the ground due to the profile of the sole
 - **Spring effect** : gives a more dynamic walk
 - **Walking assistance** : the concave structure of allows a progressive deformation of the sole in order to optimize grip and facilitate walking