

TECHNICAL DATA SHEET

Update of the document : 26/08/15
Document ISO reference : DON/LS 03.4172.B



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024
F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37
www.lemaitre-securite.com
contact@lemaitre-securite.com



SANDFOX BLACK S1 SRC
SANDAL IN BLACK GRAINED
LEATHER

PROTECTIONS FOR THIS MODEL



Sizes available from 35 to 47
Weight of one pair in size 42 : 1000 gr.
Norm EN ISO 20345 : 2011
AET : 0075/007/161/10/10/0461 ext 14/09/11

Upper features

- Upper : grained leather
- Tongue : grained leather
- Quarter lining : three-dimensional micro-porous textile
- Vamp lining : synthetic
- Counter : leather board
- Closing: scratch band
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- Toecap : polycarbonate (200 joules)

Fitting features


- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : foam and textile

Sole features

- Name : C07
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Undermine sole density : 1
- Undermine sole color : black
- Slip resistance SRA (flat) : 0,38; (heel) : 0,37
- Slip resistance SRB (flat) : 0,19 ; (heel) : 0,14

Requirements of the norm EN ISO 20345

	Steel toecap		Polycarbonate toecap		Aluminum toecap (200 joules)
	Steel midsole		Non metallic midsole		
	A	Electric resistance – Antistatic shoes.			
	CI	Insulating sole against cold.			
	E	Heel energy absorption.			
	Fo	Hydrocarbons resistance of the undermine sole.			
	HI	Insulating sole against heat.			
	HRO	Heat resistance of the sole.			
	M	Metatarsal protection.			
	P	Perforation resistance.			
	WRU	Water repellent upper.			
	WR	Water repellent junction upper/sole.			



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) \geq 0,32
SRA (heel) \geq 0,28
SRB (flat) \geq 0,18
SRB (heel) \geq 0,13

Advantages = End users benefits

- ➔ **2,0 - 2,2mm thickness leather** for better resistance (to abrasion and tearing) and longer durability.
- ➔ **Three-dimensional micro-porous textile as lining** : High breathability thanks to its structure that allows better ventilation of sweat. It is flexible and it improves comfort.
- ➔ **Non-metallic toecap made of injected polycarbonate** : invisible when worn as lightweight and ergonomic, chemically inert, elastic (in a crash, the toecape back into shape, releasing the foot easily), nonmagnetic (undetected by metal detectors) and thermal insulation (not sensitive to variation and heat transfer between -10 ° C to +40 ° C).
- ➔ **C07 sole** :
 - ✓ **Polyurethane and nitrile sole (PU/Nitrile)**. PU injected for better resistance and comfort and Nitrile resistant to high temperature by contact
 - ✓ **Heel shock absorber**
 - ✓ **Non-slip structure** with a studded open for better drainage of fluids
 - ✓ **Attack heel**, for a natural unfolding of the foot during walking and comfort while driving vehicle
 - ✓ **Open heel** for better security, especially when climbing ladders
 - ✓ **with a studded open** for better drainage of fluids