

TECHNICAL DATA SHEET

Update of the document : 26/08/15
Document ISO reference : DON/LS 03.4170.A



LEMAITRE

LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024

F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37

www.lemaitre-securite.com
contact@lemaitre-securite.com



BLUEFOX HIGH S3 SRC

ANKLE BOOT IN WATER REPELLENT

GRAINED LEATHER

PROTECTION FOR THIS MODEL



Sizes available from 35 (2) to 47(12)
Weight of one pair in size 42 (8): 1300 gr.
Norm EN ISO 20345 : 2011
CERTIFICATION N° : 0075/007/161/10/10/0461

Upper features

- Upper : water-repellent grained leather
- Collar : synthetic
- Tongue : synthetic
- Lining : three-dimensional micro-porous textile
- Vamp lining : synthetic
- Counter : leather board
- Closing : metallic fasteners
- Laces : polyamide
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- Toecap : non-metallic polycarbonate (200 joules)
- Midsole : steel (1100 Newtons)

Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : texon
- Footbed : foam and textile

Sole features

- Name : C07
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Undermine sole density : 1
- Undermine sole color : black
- Slip resistance SRA (flat) : 0,40 ; (heel) : 0,40
- Slip resistance SRB (flat) : 0,17 ; (heel) : 0,13

Requirements of the norm EN ISO 20345

	Steel toecap		Polycarbonate toecap		Aluminum toecap (200 joules)
	Steel midsole		Non metallic midsole		
	A	A Electric resistance – Antistatic shoes.			
	CI	CI Insulating sole against cold.			
	E	E Heel energy absorption.			
	Fo	FO Hydrocarbons resistance of the undermine sole.			
	HI	HI Insulating sole against heat.			
	HRO	HRO Heat resistance of the sole.			
	M	M Metatarsal protection.			
	P	P Perforation resistance.			
	Wru	WRU Water repellent upper.			
	Wr	WR Water repellent junction upper/sole.			

Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) ≥ 0,32
SRA (heel) ≥ 0,28
SRB (flat) ≥ 0,18
SRB (heel) ≥ 0,13



Advantages = End users benefits

- **Non metallic toecap made of injected polycarbonate** : invisible when worn as lightweight and ergonomic, chemically inert, elastic (in a crash, the mouthpiece back into shape, releasing the foot easily) between -10 ° C to +40 ° C).
- **2,0 - 2,2mm thickness leather** for better resistance (to abrasion and tearing) and longer durability.
- **Three-dimensional micro-porous textile lining**, very breathable and soft for higher ventilation of the foot and improved comfort.
- **C07 sole** :
 - ✓ **Attack heel**, for a natural unfolding of the foot during walking and comfort while driving vehicle
 - ✓ **Dual density polyurethane (PU2D) injected** for better resistance and comfort
 - ✓ **Heel shape** for better security, especially when climbing ladders
 - ✓ **Heel shock absorber**
 - ✓ **Non-slip structure with a studded open** for better drainage of fluids