

TECHNICAL DATA SHEET

Update of this document : 23-01-19
ISO reference : DON/LS 03.4296.A



LEMAITRE

LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024

F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37

www.lemaitre-securite.com

contact@lemaitre-securite.com



ARON N S3 CI SRC

Low shoe in water-repellent
grain leather

PROTECTIONS FOR THIS MODEL



Available sizes from 35 (2) to 48 (13)

Weight of a pair in size 42 (8) : 1270 gr.

Norm EN ISO 20345 : 2011

Upper features

- Upper : water-repellent grain leather
- Lining : three-dimensional textile
- Vamp lining : synthetic
- Backpart : synderm
- Closing : lace
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking

Protections

- Toecap : polycarbonate (200 joules)
- Anti-perforation insert : high tenacity composite fabric « zero » penetration (1100 Newtons)

Fitting features

- Lasting insole : high tenacity composite fabric
- Insock : textile and foam

Sole features

- Name : C07
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Outsole density : 1
- Outsole color : black
- Slip resistance SRA (flat) : 0,40 ; (heel) : 0,40
- Slip resistance SRB (flat) : 0,19 ; (heel) : 0,17

Advantages = End users benefits

Safety shoe 100% non-metallic

- ➔ **2,0 - 2,2mm thickness leather** for better resistance (to abrasion and tearing) and longer durability.
- ➔ **Three-dimensional micro-porous textile as lining** : High breathability thanks to its structure that allows better ventilation of sweat. It is flexible and improves comfort.
- ➔ **Anti-perforation insert high tenacity composite fabric** : ultra-light, ultra-flexible, thermally insulating (insensitive to temperature transfers) and protects 100% of the surface of the foot.
- ➔ **Non-metallic toecap made of injected polycarbonate** : invisible when worn as lightweight and ergonomic, chemically inert, elastic (in a crash, the mouthpiece back into shape, releasing the foot easily), and thermal insulation (not sensitive to variation and heat transfer between -10 ° C to +40 ° C).
- ➔ **C07 sole** :
 - Light and flexible sole
 - Attack heel, for a natural unfolding of the foot during walking and comfort while driving vehicle
 - Dual density polyurethane (PU / PU or PU2D) injected for better resistance and comfort
 - Heel shape for better security, especially when climbing ladders
 - Heel shock absorber
 - Non-slip structure with a studded open for better drainage of fluids.

Basics and additional requirements of the norm EN ISO 20345 : 2011

Toecap

steel polycarbonate aluminium HDFC Fiber composite

- Antistatic footwear.
- Penetration resistance.
- Resistance of the outsole to hot contact.
- Water penetration and water absorption resistant upper.
- Energy absorption of seat region.
- Heat insulation of sole complex.
- Metatarsal protection.

Anti-perforation insert

stainless steel composite (high tenacity fabric)

- Resistance of the outsole to fuel oil.
- Cold insulation of sole complex.
- Water resistant footwear.

Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) ≥ 0,32 SRB (flat) ≥ 0,18
SRA (heel) ≥ 0,28 SRB (heel) ≥ 0,13

