

TECHNICAL DATA SHEET

Update of the document : 28/04/2016
ISO reference of the document: DON/LS 03.4222.A



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024
F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37
www.lemaitre-securite.com
info@lemaitre-securite.com



PINK S1P SRC

LOW SHOE IN GREY MICROFIBER

PROTECTIONS FOR THIS MODEL



Available sizes : from 37 (4) to 42 (8)
Poids par paire taille 37 : 760 gr.

Norm EN ISO 20345 : 2011
AET N° 0075/007/161/06/15/0623

Upper features

- Upper : grey microfiber
- Tongue : grey microfiber
- Quarter lining : multicolor three-dimensional micro-porous textile
- Vamp lining : synthetic
- Backpart : synderm
- Closing : plastic eyelets
- Laces : polyamid
- Tongue markings : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections 100% COMPOSITE

- Toecap : polycarbonate
- Anti-perforation insert : high tenacity composite fabric « 0 » penetration

Fitting features

- Lasting insole : textile
- Footbed : foam and textile

Sole features

- Name : PARABOLIGHT
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Outsole density : 1
- Outsole color : black
- Slip resistance SRA (flat) : 0,33 ; (heel) : 0,36
- Slip resistance SRB (flat) : 0,23; (talon) : 0,21



Basics and additional requirements of the norm EN ISO 20345 : 2011

- Steel toecap
- Polycarbonate toecap
- Aluminium toecap (200 joules)
- Stainless steel composite (high tenacity fabric)
- A** Antistatic footwear.
- CI** Cold insulation of sole complex.
- E** Energy absorption of seat region.
- Fo** FO Resistance of the outsole to fuel oil.
- Hi** HI Heat insulation of sole complex.
- Hro** HRO Resistance of the outsole to hot contact.
- M** M Metatarsal protection.
- P** P Penetration resistance
- Wru** WRU Water penetration and water absorption resistant upper.
- Wr** WR Water resistant footwear.

Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :

SRA (flat) ≥ 0,32
SRA (heel) ≥ 0,28
SRB (flat) ≥ 0,18
SRB (heel) ≥ 0,13



Advantages = End users benefits

Trendy safety shoe for women
with 100% composite protections.

- **Well-fitting adapted to the morphology of the female foot.**
- **Grey microfiber** : Light, flexible and very resistant to abrasion. This material gives a pleasant sensation of comfort.
- **Three-dimensional micro-porous textile as lining** : High breathability thanks to its structure that allows better ventilation of sweat. It is flexible and it improves comfort.
- **Anti-perforation insert high tenacity composite fabric « 0 » penetration** : ultra-light, ultra-flexible (insensitive to worn), thermally insulating (insensitive to temperature transfers) and protects 100% of the surface of the foot.
- **Polyurethane with good properties** : good antistatic properties and good resistance to hydrolysis and heat.
- **PARABOLIGHT sole** :
 - ✓ **Slip resistant** sole thanks to a structured drawing "winter tire" design, which allows a quick evacuation of liquids.
 - ✓ **Special design to suit the shape of women's feet for a better fit.**
 - ✓ Polyurethane Double Density (PU2D) injected : **the best dual density** polyurethanes for the insole and outsole.
- **PARABOLIC® sole** :
 - ✓ **Exceptional grip** : the concave structure of the sole allows progressive bending of the sole in order to optimize grip.
 - ✓ **Comfort when walking** : the spring effect gives a more dynamic walk and facilitates walking.
 - ✓ **Anti-fatigue** : with every step, the recycled energy gives you a spring in your step and provides anti-fatigue effect to your legs.