

TECHNICAL DATA SHEET

UPDATMENT of the document : 29/06/2015
ISO reference of the document : DON/LS 03.917.C



LEMAITRE

LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024

F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37
www.lemaitre-securite.com
info@lemaitre-securite.com



NADINE S3 SRC
LADIES SHOE WITH BLACK WATER-
REPELLENT FULL GRAIN LEATHER

PROTECTION FOR THIS MODEL



Sizes available from 35 (2) to 42 (8)
Weight of one pair in size 38 : 900 gr.
Norme EN ISO 20345 : 2011
AET : 0161/19250/12



Upper features

- Upper : water repellent full grain leather
- Tongue lining : leather and Cambrelle®
- Lining : Cambrelle®
- Vamp lining : synthetic
- Counter : synderme
- Closing : textile fastenings and metallic eyelets
- Laces : polyamide
- Tongue marking: size, manufacturer, manufacture date (month, date), norm, protection, CE marking.

Protections

- Toecap : stainless steel (200 Joules)
- Midsole : stainless steel (1100 Newtons)

Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : foam and textile

Sole features

- Name : PARABOLINE
- Material : double density polyurethane
- Comfort sole density : 0,5
- Color comfort sole : darkgrey
- Undermine sole density : 1
- Color undermine sole : black
- Slipping resistance SRA (flat) : 0,45 ; (heel) : 0,42
- Slipping resistance SRB (flat) : 0,22 ; (heel) : 0,18

Basics and additional requirements of the norm EN ISO 20345 : 2011

	Steel toecap		Polycarbonate toecap		Aluminium toecap (200 joules)
	Stainless steel		composite (high tenacity fabric)		
	A	Antistatic footwear.			
	Ci	Cold insulation of sole complex.			
	E	Energy absorption of seat region.			
	Fo	Resistance of the outsole to fuel oil.			
	Hi	Heat insulation of sole complex.			
	Hro	Resistance of the outsole to hot contact.			
	M	Metatarsal protection.			
	P	Penetration resistance			
	Wru	Water penetration and water absorption resistant upper.			
	Wr	Water resistant footwear.			



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) = 0,32
SRA (heel) = 0,28
SRB (flat) = 0,18
SRB (heel) = 0,13

Advantages = end users benefits

- ➔ **Well fitting adapted to the morphology of the female foot.**
- ➔ **CAMBRELLE® lining:** offers greater comfort and hygiene. 100% polyamide, this material is breathable, transferring humidity from the skin to the outside. It is also highly resistant to abrasion.
- ➔ **Polyurethane with good properties :** good antistatic properties and good resistance to hydrolysis and heat.
- ➔ **Excellent slip resistance** due to the profile of the sole which adapts to the nature of the ground.
 - ✓ **A sole designed for women**
 - ✓ **Heel shock absorber**
 - ✓ **Insulating against cold.**
 - ✓ **Double density polyurethane (injected)**
- ➔ **PARABOLIC® sole :**
 - ✓ **Exceptional grip :** the concave structure of the sole allows progressive bending of the sole in order to optimize grip.
 - ✓ **Comfort when walking :** the spring effect gives a more dynamic walk and facilitates walking.
 - ✓ **Anti-fatigue :** with every step, the recycled energy gives you a spring in your step and provides anti-fatigue effect to your legs.