

TECHNICAL DATA SHEET

Update of the document : 15/06/2015
ISO reference of the document: DON/LS 03.4137.A



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024
F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37
www.lemaitre-securite.com
info@lemaitre-securite.com



WANTED S1P SRC

HIGH SHOE IN ABRASION RESISTANT TEXTILE
WITH SOLE PU/PU

PROTECTIONS FOR THIS MODEL



Available sizes : from 38 (5) to 47 (12)
Poids par paire taille 42 (8) : 1100 gr.

Norm EN ISO 20345 : 2011
Certificate n° : LEC FI00347945
(Extension of certificate LEC FI00341933)



Upper features

- Upper : abrasion resistant textile
- Tongue : abrasion resistant textile
- Quarter lining : black three-dimensional micro-porous textile
- Vamp lining : synthetic
- Backpart : synderm
- Closing : plastic eyelets
- Laces : polyamid
- Tongue markings : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- Toecap : aluminium
- Anti-perforation insert : high tenacity composite fabric « 0 » penetration

Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : foam and textile

Sole features

- Name : STREET
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : black
- Outsole density : 1
- Outsole color : light grey
- Slip resistance SRA (flat) : 0,42 ; (heel) : 0,40
- Slip resistance SRB (flat) : 0,30; (talon) : 0,16

Basics and additional requirements of the norm EN ISO 20345 : 2011

	Steel toecap		Polycarbonate toecap		Aluminium toecap (200 joules)
	Stainless steel composite (high tenacity fabric)				
	A Antistatic footwear.				
	CI Cold insulation of sole complex.				
	E Energy absorption of seat region.				
	FO Resistance of the outsole to fuel oil.				
	HI Heat insulation of sole complex.				
	HRO Resistance of the outsole to hot contact.				
	M Metatarsal protection.				
	P Penetration resistance				
	WRU Water penetration and water absorption resistant upper.				
	WR Water resistant footwear.				



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :

SRA (flat) ≥ 0,32
SRA (heel) ≥ 0,28
SRB (flat) ≥ 0,18
SRB (heel) ≥ 0,13

Advantages = End users benefits

Trendy safety shoe with an urban style for men.

- **Upper in printed textile "camouflage style" and leather** : this textile in trendy printing is very resistant to abrasion and leather offer a longer life to the product.
- **Three-dimensional micro-porous textile as lining** : High breathability thanks to its structure that allows better ventilation of sweat. It is flexible and it improves comfort.
- **Toecap in aluminium** : insensitive to worn, ultra-light and large, it is ergonomic.
- **Anti-perforation insert high tenacity composite fabric « 0 » penetration** : ultra-light, ultra-flexible (insensitive to worn), thermally insulating (insensitive to temperature transfers) and protects 100% of the surface of the foot
- **Polyurethane with good properties** : good antistatic properties and good resistance to hydrolysis and heat.
- **The top of the shoe is made of PU coating for a better life of the shoe.**
- **STREET sole** :
 - ✓ **PU2D** : the best dual density polyurethanes for the insole and outsole which allows a better resistance.
 - ✓ **Flat sole** for greater stability.
 - ✓ **Shock absorber at the heel.**
 - ✓ **Tread design slip-resistant sole.**