

# TECHNICAL DATA SHEET

Update of the document : 26/06/2015  
ISO reference of the document: DON/LS.4119.B



LEMAITRE SECURITE SAS  
17 rue Bitschhoffen  
CS 90024  
F 67350 La Walck FRANCE  
Tél. : +33 (0)3 88 72 28 80  
Fax : +33 (0)3 88 07 05 37  
[www.lemaitre-securite.com](http://www.lemaitre-securite.com)  
[info@lemaitre-securite.com](mailto:info@lemaitre-securite.com)



**VEGA S3 SRC**  
ETERNALLY CLASSIC BROGUES  
IN WATER-REPELLENT FULL  
GRAIN LEATHER  
100% NON-METALLIC

## PROTECTIONS FOR THIS MODEL



Sizes available : from 38 (5) to 48 (13)  
Weight of one pair in size 42(8) : 1100 gr.  
Norm EN ISO 20345 : 2011  
CERTIFICATION N°: 0161/19253/12

## Upper features

- Upper : water-repellent full grain leather
- Tongue : water-repellent full grain black leather
- Lining : Cambrelle®
- Vamp lining : synthetic
- Backpart : synderm
- Closing: laces without eyelets
- Laces : polyamide
- Tongue markings: size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

## Protections

- Toecap : polycarbonate (200 joules)
- Midsole : High tenacity composite fabric "0" penetration (1100 N)

## Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : foam and textile

## Sole features

- Name : CITY
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Outsole density : 1
- Outsole color : black
- Slip resistance SRA (flat) : 0,47; (heel) : 0,50
- Slip resistance SRB (flat) : 0,21 ; (heel) : 0,20

## Basics and additional requirements of the norm EN ISO 20345 : 2011

	Steel toecap		Polycarbonate toecap		Aluminium toecap (200 joules)
	Steel midsole		Non-metallic midsole		
	A	A Electric resistance – Antistatic shoes.			
	Ci	Ci Insulating sole against cold.			
	E	E Heel energy absorption.			
	Fo	FO Hydrocarbons resistance of the undermine sole.			
	Hi	HI Insulating sole against heat.			
	Hro	HRO Heat resistance of the sole.			
	M	M Metatarsal protection.			
	P	P Perforation resistance.			
	Wru	WRU Water repellent upper.			



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :  
SRA (flat)  $\geq 0,32$   
SRA (heel)  $\geq 0,28$   
SRB (flat)  $\geq 0,18$   
SRB (heel)  $\geq 0,13$

## Advantages = End users benefits

### Eternally classic brogues with 100 % non-metallic protections

- ➔ **Leather 1.6-1.8 mm thickness** for a better mechanical resistance (abrasion, tearing and perforation) and durability.
- ➔ **Elegant design.**
- ➔ **Wide, extremely comfortable fit.**
- ➔ **Composite toecap** made of injected polycarbonate, ergonomic, light, elastic and thermic insulation (not sensitive to variation and heat transfer between -10°C to 40°C).
- ➔ **Cambrelle® lining**, offers greater comfort and hygiene. 100% polyamide. Very breathable, transferring humidity from the skin to the outside. It is also highly resistant to abrasion.
- ➔ **Anti-perforation insert high tenacity composite fabric « 0 » penetration** : ultra-light, ultra-flexible (insensitive to worn), thermally insulating (insensitive to temperature transfers) and protects 100% of the surface of the foot.
- ➔ **Dual density polyurethane sole PU2D** : very versatile with good antistatic properties, resistance to hydrolysis and heat and shock absorption.
- ➔ **SOLE CITY :**
  - ✓ **Slip resistant sole**
  - ✓ **Dual density PU** : excellent comfort even in extreme flexing conditions
  - ✓ **Defined heel** : sure-footed safety! an additional precaution especially on ladders
  - ✓ **Heel shock absorber** for better comfort
  - ✓ **Very resistant to landslides** thanks to the studded open structure for better drainage of liquids
  - ✓ **Elegant sole**
  - ✓ **Antistatic**