

TECHNICAL DATA SHEET

UPDATEMENT of the document : 15/02/2013
Référence ISO de ce document : DON/LS 03



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024

F 67350 La Walck FRANCE

Tél. : +33 (0)3 88 72 28 80

Fax : +33 (0)3 88 07 05 37

www.lemaitre-securite.com

contact@lemaitre-securite.com



SPEEDSTER S3 CI SRC

LOW SHOE IN WATER REPELLENT FULL
GRAIN LEATHER

PROTECTION FOR THIS MODEL



Sizes available from 35 (2) to 48(13)
Weight of one pair in size 42 (8): 1270 gr.
Norm EN ISO 20345 : 2011
AET N° 0075/007/161/07/13/0633
EXT 20/10/13

Upper features

- Upper : water repellent full grain leather
- Collar : synthetic
- Tongue : leather and Cambrelle
- Lining : Cambrelle
- Vamp lining : synthetic
- Counter : leather board
- Eyelet : non metallics
- Laces : polyamide
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- Toecap : stainless steel (200 joules)
- Midsole : stainless steel (1100 Newtons)

Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : polyurethane

Sole features

- Name : Sporty
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Undermine sole density : 1
- Undermine sole color : black
- Slip resistance SRA (flat) : 0,46 ; (heel) : 0,43
- Slip resistance SRB (flat) : 0,26 ; (heel) : 0,20

Requirements of the norm EN ISO 20345 : 2011

Steel toecap Polycarbonate toecap Aluminum toecap (200 joules)

Steel midsole Non metallic midsole

A A Electric resistance – Antistatic shoes.

CI CI Insulating sole against cold.

E E Heel energy absorption.

Fo FO Hydrocarbons resistance of the undermine sole.

Hi HI Insulating sole against heat.


Hro HRO Heat resistance of the sole.

M M Metatarsal protection.

P P Perforation resistance.

Wru WRU Water repellent upper.

Wr WR Water repellent junction upper/sole.



Regarding the norm EN ISO 20345 : 2007, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) = 0,32
SRA (heel) = 0,28
SRB (flat) = 0,16
SRB (heel) = 0,12

Advantages = End users benefits

2,0-2,2mm thickness leather for better resistance (to abrasion and tearing) and longer durability.

Cambrelle lining, offers greater comfort and hygiene. 100% polyamide, this material is breathable, transferring humidity from the skin to the outside. It is also highly resistant to abrasion.

Sporty sole :

- **Attack heel**, for a natural unfolding of the foot during walking and comfort while driving vehicle
- **Comfort sole** : very thick sole at the heel
- **Dual density polyurethane (PU2D)** injected
- **Sportive design**
- **Reinforcements of the PU sole** at the front and the back of the shoe for a better protection of the leather and the shoe
- **Cold insulation**
- **Heel shock absorber**
- **Non-slip structure** with a studded open for better drainage of fluids
- **Parabolic profile**
 - **Exceptional slip resistance** : footprint adapts itself to the nature of the ground due to the profile of the sole
 - **Spring effect** : gives a more dynamic walk
 - **Walking assistance** : the concave structure of allows a progressive deformation of the sole in order to optimize grip and facilitate walking
- **Sporty shape : injection of the PU sole under the foot, enables :**
 - Higher breathability of the foot
 - Adaptation of the leather to the shape of the foot
 - Flexibility of the sole