

TECHNICAL DATA SHEET

Update of this document : 06/02/2017
ISO reference : DON/LS 03.4252.A



LEMAITRE

LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024

F 67350 La Walck FRANCE

Tél. : +33 (0)3 88 72 28 80

Fax : +33 (0)3 88 07 05 37

www.lemaitre-securite.com

contact@lemaitre-securite.com



BILL S1P SRC

Sneaker in three-dimensional water-repellent textile and water-repellent suede leather and a EVA-Nitrile rubber sole

PROTECTIONS FOR THIS MODEL



Norm EN ISO 20345 : 2011

Available sizes from 38 (5) to 48 (13)

Weight of a pair in size 42 (8) : 975 gr.

AET N°0075/007/161/10/16/1148

EXT 11/12/16

Upper features

- Upper : grey three-dimensional water-repellent textile and grey water-repellent suede leather
- Tongue : grey three-dimensional water-repellent textile
- Collar : grey water-repellent suede leather
- Lining : three-dimensional textile
- Vamp lining : synthetic
- Backpart : synderm
- Closing : lace
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking

Protections

- Toecap : HDFC Fiber composite (200 joules)
- Anti-perforation insert : high tenacity composite fabric « zero » penetration (1100 Newtons)

Fitting features

- Lasting insole : high tenacity composite fabric
- Insock : textile and foam

Sole features

- Name : SP-Light
- Material : EVA / Nitrile rubber
- Comfort sole color : white and grey
- Hardness of comfort sole : 45 Shore A
- Outsole color : black
- Hardness of outsole : 66 Shore A
- Slip resistance SRA (flat) : 0,50 ; (heel) : 0,51
- Slip resistance SRB (flat) : 0,20 ; (talon) : 0,14



Advantages = End users benefits

Sneaker in the running style, ultra-light (less than one kilogram the pair) and comfortable, perfect for indoors: transport, logistic, handling, distribution, small industry, small business sector, interior work, services and administration.

- ➔ **Suede leather** : soft leather in trendy colors, noble and very strong material.
- ➔ **Three-dimensional textile** : light and breathable.
- ➔ **Three-dimensional micro-porous textile as lining** : High breathability thanks to its structure that allows better ventilation of sweat. It is flexible and improves comfort.
- ➔ **Anti-perforation insert high tenacity composite fabric** : ultra-light, ultra-flexible, thermally insulating (insensitive to temperature transfers) and protects 100% of the surface of the foot.
- ➔ **A very comfortable fitting** : large and quilted, excellent drop shot during walking.
- ➔ **SP-Light toecap** : non-metallic, non-magnetic, no heat or cold conduction.
- ➔ **SP-Light sole** :
 - ✓ EVA-Nitrile rubber sole, flexible and light, developed by Lemaitre and manufactured in Europe.
 - ✓ Outsole in Nitrile rubber : excellent abrasion resistance, to hydrocarbons and resist to very high temperatures.
 - ✓ Comfort sole in EVA is flexible and assure a good absorption to impacts.
 - ✓ Very good slip resistance thanks to an open studded structure which allows a quick and better evacuation of liquids. Optimal slip resistance on very smooth and wet grounds.
 - ✓ Very flexible sole without lateral constraint for comfort and an excellent breathing of the foot.
 - ✓ Reinforcements on the top of the shoe for protection and longer life of product.

Basics and additional requirements of the norm EN ISO 20345 : 2011

Toecap

steel polycarbonate aluminium HDFC Fiber composite

- (A)** Antistatic footwear.
- (E)** Energy absorption of seat region.
- (P)** Penetration resistance.
- (Hi)** Heat insulation of sole complex.
- (Hro)** Resistance of the outsole to hot contact.
- (M)** Metatarsal protection.
- (Wru)** Water penetration and water absorption resistant upper.

Anti-perforation insert

stainless steel composite (high tenacity fabric)

- (Fo)** Resistance of the outsole to fuel oil.
- (Ci)** Cold insulation of sole complex.
- (Wr)** Water resistant footwear.

Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) ≥ 0,32 SRB (flat) ≥ 0,18
SRA (heel) ≥ 0,28 SRB (heel) ≥ 0,13

