

TECHNICAL DATA SHEET

UPDATEMENT of the document : 22/05/14
Référence ISO de ce document : DON/LS 03



CHERRY S1P SRC

LOW TEXTILE SPORT SHOE

PROTECTION FOR THIS MODEL



Sizes available from 38 (5) to 48(13)
Weight of one pair in size 42 (8): 1170 gr.
Norm EN ISO 20345 : 2011
AET : 0075/007/161/07/13/0633
EXT 36/12/13

Upper features

- Upper : tridimensional textile with leather coated
- Tongue : tridimensional textile
- Quarter lining : tridimensional textile
- Vamp lining : synthetic
- Counter : leather board
- Closing : plastic eyelets
- Laces : polyamide in red color
- Tongue marking: size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- Toecap : stainless steel (200 joules)
- Midsole : stainless steel (1100 Newtons)




Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : texon
- Footbed : foam and polyurethane

Sole features

- Name : Sporty
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Undermine sole density : 1
- Undermine sole color : black
- Slip resistance SRA (flat) : 0,49 ; (heel) : 0,37
- Slip resistance SRB (flat) : 0,29 ; (heel) : 0,19

Requirements of the norm EN ISO 20345 : 2011

 Steel toe cap  Polycarbonate toe cap  Aluminum toe cap (200 joules)

 Steel midsole  Non metallic midsole

A A Electric resistance – Antistatic shoes.

Ci Ci Insulating sole against cold.

E E Heel energy absorption.

Fo FO Hydrocarbons resistance of the undermine sole.

Hi HI Insulating sole against heat.


Hro HRO Heat resistance of the sole.

M M Metatarsal protection.

P P Perforation resistance.

Wru WRU Water repellent upper.

Wr WR Water repellent junction upper/sole.



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) ≥ 0,32
SRA (heel) ≥ 0,28
SRB (flat) ≥ 0,18
SRB (heel) ≥ 0,13

Advantages = End users benefits

Very light and comfortable shoe thanks to the suppleness of the textile

- **Tridimensional textile lining**, soft and very breathable for better comfort
- **Leather coated anti-abrasion on the periphery of the shoe** : reduces wear and tear especially when footwear is used in flexion
- **Special toe cap (ABG) : exclusive LEMAITRE toe cap, asymmetric that matches the shape of the foot** for an elegant design and **wide for greater interior volume** and therefore a better comfort
- **Sporty sole** :
 - ✓ **Attack heel**, for a natural unfolding of the foot during walking and comfort while driving vehicle
 - ✓ **Dual density polyurethane (PU2D) injected**
 - ✓ **Heel shock absorber and very thick sole at the heel** for better comfort
 - ✓ **Reinforcements of the PU sole** at the front and the back of the shoe for a better protection of the leather and the shoe
 - ✓ **Cold insulation**
 - ✓ **Sportive design**
 - ✓ **Non-slip structure** with a studded open for better drainage of fluids
- **Parabolic profile**

- ✓ **Exceptional slip resistance** : footprint adapts itself to the nature of the ground due to the profile of the sole
- ✓ **Spring effect** : gives a more dynamic walk
- ✓ **Walking assistance** : the concave structure of allows a progressive deformation of the sole in order to optimize grip and facilitate walking
- ➔ **Sporty shape : injection of the PU sole under the foot, enables :**
 - ✓ **Adaptation of the leather to the shape of the foot**
 - ✓ **Higher breathability of the foot**
 - ✓ **Flexibility of the sole**